

Hegrecat® PMDETA

General Description

Hegrecat® PMDETA is the industrial standard blowing (water – isocyanate) catalyst.

Product Property

- Strongly promotes blowing reaction
- Hydrolytically stable

Applications

PMDETA is commonly used in many rigid foam application such as appliance and construction panel. Use of PMDETA improves the blowing reaction which helps the flow of the rigid foam

Typical Physical Property

Appearance	Colorless liquid
Flash Point, °C (PMCC)	72
Viscosity at 25°C	3
Specific Gravity at 25°C	0.85
Water Solubility	soluble
Calculated OH number [mgKOH/g]	0

Storage and package Information

HeJia Chemical recommends that our catalysts be stored in a dry and cool area under appropriate ventilation conditions. Each container should be closed tightly to avoid contamination with moisture or other negative influences, which could change the products' performance in the end use. 170kgs per steel drum.

Shelf Life

36 months from the date of production

Disclaimer

The information contained in this TDS is believed to be accurate to the best of Hejia Chemical's knowledge and belief at the time of the TDS publication. The information is intended to be used as a guideline and for informational purpose only. Consequently we do not warrant that the information or the related products are fit for any particular purpose or use by users and it is user's responsibility to test and confirm the fitness of the product.

Hejia shall NOT BE LIABLE, whether contractually or in tort, for damages caused through the use or the reliance on this information and/or the related products.